

TECHNICAL DATASHEET

REV.00

6X3000000

U+DC


FEATURES:

- Panoramic lens can be perfectly worn over prescription glasses
- Exclusive UDC coating
- Facial support compatible with half masks
- Additional facial protection
- Indirect ventilation system assures certified protection against drops and splashes
- Category III° PPE
- Impact resistance at 432 km/h, even at extreme temperatures

FEATURES FRAME:

Frame Typology	Mask
PPE field of view	>40
Complete PPE weight (g)	75
Size (mm)	158
Frame Features	Polypropylene/TPR
Elastic Band Features	Elastic tissue
Ventilation System	Indirect Ventilation

FEATURES OCULARS/LENSES:

VLT% (+/-5%)	91.2
Material Ocular/Flip-up	Polycarbonate
Colour	Clear
Technical Treatment	U + DC
Thickness [mm](+/- 0.1)	1.9
Curvature	Base 5,0 Spheric
Optical Class	1
UV Protection	380
Spare parts	-

MARKS:

Standard Reference	EN166 EN170
Frame Marking	U EN166 3 4 9 BT 0068 CE
Ocular/Flip-up Marking	2C-1.2 U 1 BT 9 K N 0068 CE

FIELDS OF EMPLOYMENT

Protection against droplets and splashes of liquids (3); Protection against high-speed particles at extreme temperatures (T); Protection against high-speed particles - low energy (F); Protection against large dust particles (>0.5 um) (4); Protection against molten metals and hot solids (9); Resistance to fogging of oculars (N); Resistance to surface damage by fine particles (K)

Notes

