

3036UE



## 2- door tall safety cabinet Type 30

### COMPLIANCE

EN 14470-1, FM 6050

### ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

### BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable leveling feet for enhance stability
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Pedestal area under-driveable by a forklift by removing panel
- Tested and approved according to FM 6050



### TECHNICAL FEATURES

Model	<b>3036UE</b>	Shipping dimensions HxWxD (mm)	<b>1971 x 1200 x 1000</b>
Compliance	<b>EN 14470-1, FM 6050</b>	Ventilation	<b>Both inlet and outlet on the back wall of the cabinet</b>
Cabinet materials	<b>Melamine wood structure</b>	Openings diameter (mm)	<b>100</b>
Doors color	<b>light grey RAL 7035</b>	Number of compartments	<b>1</b>
Number of doors	<b>2</b>	Containment sump	<b>1</b>
Doors type	<b>swing doors</b>	HS Code	<b>210.00</b>
Hinges	<b>right &amp; left</b>		<b>94036000</b>
Door closure	<b>self-closing</b>		

### ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

### OPTIONS

- Containment sump for cabinet 3036UE (Réf : B6U)
- Retention shelf for cabinet 3036UE (Réf : E6U)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
3036UE	1731 x 864 x 864	1330 x 750 x 730	228		2	50	210.00