

795+LIX4



# Safety cabinet 90 min for lithium batteries High 2 doors + VIG290 + 4 E35LI

## COMPLIANCE

## ADVANTAGES

- 105-minute fire resistant and made in France
- Storage of flammables
- Storage of lithium-ion batteries

### BUT ALSO...

- Locking system
- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Reduce the risk of fire and explosion
- 105-minute fire resistant and made in France



## TECHNICAL FEATURES

Model	<b>795+LIX4</b>	Ventilation	<b>Both inlet and outlet on the top of the cabinet</b>
Doors color	<b>white RAL 9010</b>	Openings diameter (mm)	<b>100</b>
Number of doors	<b>2</b>	Connecting sleeve	<b>1</b>
Doors type	<b>swing doors</b>	Number of compartments	<b>1</b>
Hinges	<b>left and right</b>	HS Code	<b>488.00</b>
Door closure	<b>automatic closing</b>		<b>94032080</b>
Shipping dimensions HxWxD (mm)	<b>2150 x 1200 x 800</b>		

## ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Containment sump for 2-door cabinets Types 30, 60 & 90 (Réf : B235)
- Rack of 9 electrical outlets (Réf : PRISELI)
- Perforated cover plate for 2-door safety cabinets Types 30, 60 & 90 (Réf : C235)
- Breakthrough for cable entry with fire-resistant cable (Réf : PEXTBALI)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Rack of 6 electrical outlets equipped with a thermal-magnetic circuit breaker (Réf : PRISELICC)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)
- Perforated shelf for 2-door safety cabinet (Réf : E35LI)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
795+LIX4	1950 x 1137 x 620	1620 x 1000 x 410	0		4	100	488.00