

# 1- door working cover safety cabinet Type 90

## COMPLIANCE

EN 14470-1, EN 1363-1

## ADVANTAGES

- 105-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

### BUT ALSO...

- Thermo-expanding seals of the doors
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory
- Adjustable shelves in height



## TECHNICAL FEATURES

Model	<b>798+E</b>	Shipping dimensions HxWxD (mm)	<b>1300 x 1200 x 800</b>
Compliance	<b>EN 14470-1, EN 1363-1</b>	Ventilation	<b>Both inlet and outlet on the back wall of the cabinet</b>
Cabinet materials	<b>12/10th epoxy painted steel structure</b>	Openings diameter (mm)	<b>100</b>
Doors color	<b>white RAL 9010</b>	Number of compartments	<b>1</b>
Number of doors	<b>1</b>	Containment sump	<b>1</b>
Doors type	<b>swing doors</b>	HS Code	<b>182.00</b>
Hinges	<b>right</b>		<b>94032080</b>
Door closure	<b>self-closing</b>		

## ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

## OPTIONS

- Containment sump for 1- door cabinets Types 30, 60 & 90 (Réf : B148)
- Perforated cover plate for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : C148)
- Retention shelf for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : E48)
- Containment sump in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SB148)
- Protection shelf in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SE148)
- Sliding drawer for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : T148)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
798+E	1100 x 635 x 670	820 x 490 x 410	65		2	30	182.00