

## 2- door underbench safety cabinet Type 90

### COMPLIANCE

EN 14470-1, EN 1363-1

### ADVANTAGES

- 105-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

### BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable shelves in height
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory



### TECHNICAL FEATURES

Model	<b>792+E</b>	Shipping dimensions HxWxD (mm)	<b>900 x 1200 x 800</b>
Compliance	<b>EN 14470-1, EN 1363-1</b>	Ventilation	<b>Both inlet and outlet on the back wall of the cabinet</b>
Cabinet materials	<b>12/10th epoxy painted steel structure</b>	Openings diameter (mm)	<b>100</b>
Doors color	<b>white RAL 9010</b>	Number of compartments	<b>1</b>
Number of doors	<b>2</b>	Containment sump	<b>1</b>
Doors type	<b>swing doors</b>	HS Code	<b>213.00</b>
Hinges	<b>right &amp; left</b>		<b>94032080</b>
Door closure	<b>self-closing</b>		

### ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
792+E	630 x 1137 x 570	420 x 1000 x 285	60		1	50	213.00