



Fall protection

LO047150AD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

Certifications and norms

EN354



Protects against risks



Fall



LO047150AD

LANYARDS

Fall protection

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Standards - Details

Technical details

Type of equipment	Braided rope
Composition of the main support	Glass-fibre
Length	1,5 m
Rope diameter	10,5 mm
With connector	yes
Color	White
Connector (user side)	Automatic lock hook, steel, opening 16mm
SIZE	1.50 m
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing	10 years
Weight	0,802 kg
Fall arrest work situations	Restraint



Fall protection

LO047150AD

LANYARDS

1.5 metre lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
LO047150AD	White	1.50 m	LO047150AD	3660348006354	13660348006351	5	1	4.7 kg